

SPRINTER CREW



TECHNICAL SPECIFICATIONS: 2500 & 3500

Tires	2500				3500		
	Single		170"		Dual Rear Wheel		Super Single
Wheelbase	144"		170"		144"	170"	170"
Engine	Gas/Diesel	Diesel	Gas/Diesel	Diesel	Diesel	Diesel	Diesel
Drivetrain	4x2	4x4	4x2	4x4	4x2	4x2	4x2
Roof height	High Roof	High Roof	High Roof	High Roof	High Roof	High Roof	High Roof
Passenger capacity	5	5	5	5	5	5	5
Rows of seats	Two	Two	Two	Two	Two	Two	Two

EXTERIOR

Length	233.5"	233.5"	274.3"	274.3"	233.5"	274.3"	274.3"
Height	107.5"	111.3"	107.3"	111.3"	109.1"	108.7"	109.1"
Width - excluding mirrors	79.5"	79.5"	79.5"	79.5"	79.5"	79.5"	79.5"
Width - including mirrors	92.3"	92.3"	92.3"	92.3"	92.3"	92.3"	92.3"
Tire track front	67.2"	67.8"	67.2"	67.8"	66.5"	66.5"	67.2"
Tire track rear	68.2"	68.2"	68.2"	68.2"	60.7"	60.7"	65.2"
Front overhang BA	40.2"	40.2"	40.2"	40.2"	40.2"	40.2"	40.2"
Rear overhang (rear axle to end of frame)	49.1"	49.1"	63.8"	63.8"	49.1"	63.8"	63.8"
Load height, unloaded (ground to cargo floor)	27.4" G	31.4"	27.3" G	31.1"	28.5"	28.1"	28.1"
	27.6" D		27.4" D				
Load height, loaded (ground to cargo floor)	23.3"	26.8"	23.4"	26.8"	23.2"	23.2"	23.2"
Side-door opening height	71.6"	71.6"	71.6"	71.6"	71.6"	71.6"	71.6"
Side-door opening width - sliding	51"	51"	51"	51"	51"	51"	51"
Rear cargo door opening height	72.7"	72.7"	72.7"	72.7"	72.7"	72.7"	72.7"
Rear cargo door opening width	61.2"	61.2"	61.2"	61.2"	61.2"	61.2"	61.2"
Turning radius (curb-to-curb)	40.7'	43.3'	47.2'	50.2'	45.3'	52.5'	52.5'
Ground to first step-side	20.8"	24.7"	20.4"	24.2"	21.6"	20.9"	20.9"

INTERIOR

Headroom (1st row)	56.4"	56.4"	56.4"	56.4"	56.4"	56.4"	56.4"
Shoulder room (1st row)	67.4"	67.4"	67.4"	67.4"	67.4"	67.4"	67.4"
Hip room (1st row)	63.7"	63.7"	63.7"	63.7"	63.7"	63.7"	63.7"
Legroom (1st row)	38.9"	38.9"	38.9"	38.9"	38.9"	38.9"	38.9"
Cargo length, front (at floor)	TBD	TBD	TBD	TBD	TBD	TBD	TBD
Cargo length, front (at belt)	TBD	TBD	TBD	TBD	TBD	TBD	TBD
Cargo width between wheelhouses	53.1"	53.1"	53.1"	53.1"	38.5"	38.5"	48.4"
Cargo height, maximum (with trim)	TBD	TBD	TBD	TBD	TBD	TBD	TBD
Maximum floor width	70.4"	70.4"	70.4"	70.4"	70.4"	70.4"	70.4"
Interior standing height	76.7"	76.7"	76.7"	76.7"	76.7"	76.7"	76.7"

CARGO CAPACITY

Cargo volume (behind last row of seats)	261.3 cu. ft.	261.3 cu. ft.	370.8 cu. ft.	370.8 cu. ft.	261.3 cu. ft.	370.8 cu. ft.	370.8 cu. ft.
Maximum roof load	330 lbs.	330 lbs.	330 lbs.	330 lbs.	330 lbs.	330 lbs.	330 lbs.
Maximum available GCWR	TBD	TBD	TBD	TBD	TBD	TBD	TBD

MAXIMUM CAPABILITIES

Maximum payload	TBD	TBD	TBD	TBD	TBD	TBD	TBD
Maximum towing ¹⁶	TBD	TBD	TBD	TBD	TBD	TBD	TBD
GVWR	9,050 lbs.	9,050 lbs.	9,050 lbs.	9,050 lbs.	9,990 lbs.	9,990 lbs.	9,990 lbs.
TWR (maximum loaded trailer weight ratings)	TBD	TBD	TBD	TBD	TBD	TBD	TBD

SPRINTER CREW



TECHNICAL SPECIFICATIONS: 3500XD & 4500

Tires	3500XD						4500	
	Dual Rear Wheel			Super Single			Dual Rear Wheel	
Wheelbase	144"		170"		170"		144"	170"
Engine	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel
Drivetrain	4x2	4x4	4x2	4x4	4x2	4x4	4x2	4x2
Roof height	High Roof	High Roof	High Roof	High Roof	High Roof	High Roof	High Roof	High Roof
Passenger capacity	5	5	5	5	5	5	5	5
Rows of seats	Two	Two	Two	Two	Two	Two	Two	Two

EXTERIOR

Length	233.5"	233.5"	274.3"	274.3"	274.3"	233.5"	274.3"
Height	109.1"	111.2"	108.7"	110.9"	109.1"	108.9"	108.5"
Width - excluding mirrors	79.5"	79.5"	79.5"	79.5"	79.5"	79.5"	79.5"
Width - including mirrors	95.5"	95.5"	95.5"	95.5"	95.5"	95.5"	95.5"
Tire track front	66.5"	66.8"	66.5"	66.8"	67.2"	66.0"	66.0"
Tire track rear	60.7"	60.7"	60.7"	60.7"	65.2"	60.7"	60.7"
Front overhang BA	40.2"	40.2"	40.2"	40.2"	40.2"	40.2"	40.2"
Rear overhang (rear axle to end of frame)	49.1"	49.1"	63.8"	63.8"	63.8"	49.1"	63.8"
Load height, unloaded (ground to cargo floor)	29.2"	30.6"	28.9"	30.3"	28.9"	29.0"	28.7"
Load height, loaded (ground to cargo floor)	24.5"	24.9"	24.6"	24.8"	24.6"	24.5"	24.6"
Side-door opening height	71.6"	71.6"	71.6"	71.6"	71.6"	71.6"	71.6"
Side-door opening width - sliding	51.0"	51.0"	51.0"	51.0"	51.0"	51.0"	51.0"
Rear cargo door opening height	72.7"	72.7"	72.7"	72.7"	72.7"	72.7"	72.7"
Rear cargo door opening width	61.2"	61.2"	61.2"	61.2"	61.2"	61.2"	61.2"
Turning radius (curb-to-curb)	45.3'	43.3'	52.5'	50.2'	52.5'	45.3'	52.5'
Ground to first step-side	21.6"	20.9"	21.6"	20.8"	20.8"	20.8"	20.8"

INTERIOR

Headroom (1st row)	56.4"	56.4"	56.4"	56.4"	56.4"	56.4"	56.4"
Shoulder room (1st row)	67.4"	67.4"	67.4"	67.4"	67.4"	67.4"	67.4"
Hip room (1st row)	63.7"	63.7"	63.7"	63.7"	63.7"	63.7"	63.7"
Legroom (1st row)	38.9"	38.9"	38.9"	38.9"	38.9"	38.9"	38.9"
Cargo length, front (at floor)	TBD	TBD	TBD	TBD	TBD	TBD	TBD
Cargo length, front (at belt)	TBD	TBD	TBD	TBD	TBD	TBD	TBD
Cargo width between wheelhouses	38.5"	38.5"	38.5"	38.5"	48.4"	38.5"	38.5"
Cargo height, maximum (with trim)	TBD	TBD	TBD	TBD	TBD	TBD	TBD
Maximum floor width	70.4"	70.4"	70.4"	70.4"	70.4"	70.4"	70.4"
Interior standing height	76.7"	76.7"	76.7"	76.7"	76.7"	76.7"	76.7"

CARGO CAPACITY

Cargo volume (behind last row of seats)	261.3 cu. ft.	261.3 cu. ft.	370.8 cu. ft.	370.8 cu. ft.	370.8 cu. ft.	261.3 cu. ft.	370.8 cu. ft.
Maximum roof load	330 lbs.	330 lbs.	330 lbs.	330 lbs.	330 lbs.	330 lbs.	330 lbs.
Maximum available GCWR	TBD	TBD	TBD	TBD	TBD	TBD	TBD

MAXIMUM CAPABILITIES

Maximum payload	TBD	TBD	TBD	TBD	TBD	TBD	TBD
Maximum towing ¹⁶	TBD	TBD	TBD	TBD	TBD	TBD	TBD
GVWR	11,030 lbs.	11,030 lbs.	11,030 lbs.	11,030 lbs.	11,030 lbs.	12,125 lbs.	12,125 lbs.
TWR (maximum loaded trailer weight ratings)	TBD	TBD	TBD	TBD	TBD	TBD	TBD